

DECLARATION OF PERFORMANCE Nr. 2

1.Unique identification code of the product

type: **sheet - article code: BAxxxxxxxxxxxxxx.**

The code specifies: alloy, thickness (mm), temper, width (mm), length (mm), type of surface : mill finish, thickness tolerance, type of coating.

ex. BA5D2000HA1500030000MCB (BA=sheet, 5F=alloy 5049, 2000=thickness 2mm, HA1= temper H111, 15000=width 1500 mm, 30000=length 3000 mm, M= Mill Finish, C= centre thickness tolerance, B= without coating)

In **TAB.1** – alloy identification, tempers and feasible thicknesses.

Description Sheet / plate / strip: EN 485-1 - EN 485-2 - EN 485-4														
Alloy	Temper												Thickness range (mm)	
	0 H111	H12	H22	H14	H24	H16	H26	H17	H18	H28	H19	H29		
EN 573-3														
EN AW 5754	X	X	X	X	X				X	X	(1)	(1)		0.2-6.0
EN AW 5251	X	X	X		X									0.2-6.0
EN AW 5182	X	(1)	(1)											0.2-6.0
EN AW 5052	X	X	X											0.2-6.0
EN AW 5049	X	X	X		X									0.2-6.0
EN AW 5005	X	X	X	X	X				X					0.2-6.0
EN AW 5005A	X	X	X	X	X				X					0.2-6.0
EN AW 5083	X		X						(1)					0.2-6.0
EN AW 3105		X			X	X	X	(1)	X	X	X	(1)		0.2-2.0
EN AW 3005	X	X	X	X	X	X	X	(1)	X	X				0.2-6.0
EN AW 3003					X		X		X	X				0.2-6.0
EN AW 1050A				X	X									1.0-6.0
EN AW 1200				X	X	X								1.0-4.0

(1) Mechanical characteristics previously agreed between part

TAB.1)

2. Intended use/es: internal and external load-bearing structural construction works

3.Manufacturer:

Profilglass S.p.A.,
via Meda 28, Bellocchi di Fano, 61032 (PU)
Italy

4.Authorised representative: N.A.

5. System/s of AVCP: 2+ system

6a.Harmonised standard: EN 15088:2005

Notified body/ies: Bureau Veritas

Certificate number: 1370-CPR-1296

6b.European Assessment Document: N.A.

European Technical Assessment: N.A.
Technical Assessment Body: N.A.
Notified body/ies: N.A.

7.Declared performance/s:

<i>Essential characteristics</i>	<i>Performance</i>	<i>Harmonised technical specification</i>
Shape and dimensional tolerances	Compliant. According to UNI EN 485-4	EN 15088:2005
Elongation	Compliant. According to UNI EN 485-2	
Ultimate tensile strength	Compliant. According to UNI EN 485-2	
Tensile yield strength	Compliant. According to UNI EN 485-2	
Weldability	NPD	
Bendability	Compliant. According to TAB.2	
Fatigue strength	NPD	
Dangerous substances (regulated)	Compliant. According to REACH (CE) n. 1907/2006 Regulation 2011/65/CE (RoHS) Directive	
Durability (corrosion resistant)	NPD	

Lega (Alloy) Numerical designations	Stato Fisico (Temper)						
	0 H111	H12 H22	H14 H24	H16 H26	H17	H18 H28	H19 H29
EN AW 5754	B1		B2			B4	B4
EN AW 5251	B1	B2	B2	B2		B3	
EN AW 5052		B2					
EN AW 5049	B1		B2				
EN AW 5005	B1	B2	B2			B3	
EN AW 5083	B1	B2	B2			B4	
EN AW 3105		B2	B2	B2	B3	B3	
EN AW 3005			B2	B2			
EN AW 3003						B3	
EN AW 1050			B2				
EN AW 1200			B2				

Tab. 2

8.Appropriate Technical Documentation and/or Specific Technical Documentation: N.A.



Declaration of Performance "MILL FINISH" sheets

*Pag.3 of 3
Rev.7 of 03/05/18*

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by: Giancarlo Paci, at Bellocchi di Fano, on 03/05/2018.

A handwritten signature in blue ink, consisting of several fluid, connected strokes that form a stylized name.